

Docket No. AB-131U1

**Amendments to and Listing of Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Claims 1-3 (canceled)**

**Claim 4 (previously presented)** An active electrode array comprising:

- at least four banks of active electrodes;
- wherein each bank of active electrodes includes a plurality of active electrodes;
- wherein each active electrode comprises a plurality of individual electrode contacts and an active switch integrally formed with the individual electrode contacts for individually activating the plurality of individual electrode contacts with a selected electrode stimulation current in response to electrode control signals;
- wherein the plurality of individual electrodes included within each active electrode comprises at least one lateral electrode contact and at least one medial electrode contact;
- wherein each active electrode includes a silicon die and switching circuitry hermetically sealed on the silicon die and operatively connected to the lateral and medial electrode contacts, wherein the switching circuitry responds to the electrode control signals to selectively activate one or both of the medial or lateral electrode contacts; and
- wherein all in combination with each bank of the active electrodes comprises a stack of the silicon dies of each active electrode belonging to that bank, over-molded with silastic.

**Claim 5-7 (canceled)**

**Claim 8 (previously presented)** An active electrode array comprising:

- a plurality of active electrodes;
- wherein each active electrode includes switching circuitry built into the electrode array and a plurality of individual electrode contacts that may be individually activated by electrode control signals applied to the switching circuitry, all in combination with the switching circuitry of each active electrode comprising;

Application No. 10/624,724  
Amendment B dated June 6, 2005  
Reply to Office Action mailed April 6, 2004

Page 2 of 6

Docket No. AB-131U1

decoding circuitry,  
a first switch coupled to the decoding circuitry and the at least one lateral electrode contact, and

a second switch coupled to the decoding circuitry and the at least one medial electrode contact, wherein the decoding circuitry responds to the electrode control signals and causes the first and second switches to selectively activate one or both of the medial or lateral electrode contacts.

**Claim 9 (original)** The active electrode array of Claim 8 wherein the decoding circuitry and first and second switches of each active electrode are formed on a substrate die, and wherein the medial and lateral electrode contacts of the active electrode are formed on opposing edges of the substrate die, and wherein at least four of said substrate dies are stacked and over-molded with silastic to form the active electrode array.

**Claim 10 (original)** The active electrode array of Claim 9 wherein the active electrode array comprises a plurality of active electrode banks, wherein each active electrode bank includes a plurality of active electrodes.

**Claim 11 (original)** The active electrode array of Claim 10 wherein at least one active electrode in each active electrode bank includes a built-in strain gauge, wherein the strain gauge is adapted to measure stress across the substrate die.

**Claim 12 (previously presented)** An active electrode array comprising  
a flexible carrier in which  $n+1$  wires are embedded, where  $n$  is an integer of at least 4;  
an active electrode array at or near a distal end of the flexible carrier comprising at least  $2n$  electrode contacts;  
switching circuitry located at or near the distal end of the flexible carrier adjacent the electrode contacts, said switching circuitry being responsive to control signals presented on

Docket No. AB-131U1

at least a plurality of the  $n+1$  wires so as to direct a stimulation signal presented on another of the  $n+1$  wires to a selected pair of the electrode contacts; and

means for connecting the  $n+1$  wires at a proximal end of the flexible carrier to electronic circuitry adapted to generate the control signals and stimulation signal;

whereby at least  $2n$  electrodes located at the distal end of the flexible carrier may be connected for individual control through no more than  $n+1$  wires embedded within the flexible carrier; and wherein the switching circuitry of each active electrode comprises:

decoding circuitry,

a first switch coupled to the decoding circuitry and the lateral electrode contact, and

a second switch coupled to the decoding circuitry and the medial electrode contact, wherein the decoding circuitry responds to the electrode control signals and causes the first and second switches to selectively activate one or both of the medial or lateral electrode contacts.

**Claim 13 (original)** The active electrode array as set forth in Claim 12 wherein the at least  $2n$  electrode contacts included within the active electrode array comprises at least  $n$  lateral electrode contacts and at least  $n$  medial electrode contacts.

**Claim 14 (original)** The active electrode array as set forth in Claim 13 wherein the switching circuitry comprises a silicon die on which switching circuitry has been formed and hermetically sealed and operatively connected to the lateral and medial electrode contacts, wherein the switching circuitry responds to the electrode control signals to selectively activate selected ones of the medial or lateral electrode contacts.

**Claim 15 (canceled)**

**Claim 16 (previously presented)** The active electrode array of Claim 12 wherein the decoding circuitry and first and second switches of each active electrode are formed on a substrate die, and wherein the medial and lateral electrode contacts of the active electrode are formed on

Application No. 10/624,724  
Amendment B dated June 6, 2005  
Reply to Office Action mailed April 6, 2004

Page 4 of 6

Docket No. AB-131U1

opposing edges of the substrate die, and wherein at least four of said substrate dies are stacked and over-molded with silastic to form the active electrode array.

Application No. 10/824,724  
Amendment B dated June 6, 2005  
Reply to Office Action mailed April 6, 2004

Page 5 of 6